

Stehle Product Information

PARAT - NEGATIVE HKS

UNIVERSAL SAW BLADE HW - NEGATIVE HOOK ANGLE „TR-F“




- clipping and miter saws
- portable saws



- for many applications and materials (wood-based panels and NF-materials)

- tooth configuration: triple chip / flat "TR-F"
- cutting material: HW TC10

- negative hook angle for high cutting quality and safe handling



well suited for:
facade & roofing, seals and insulation
wall and ceiling, acoustics / sound
insulation, flooring



well suited for:
OSB, laminated particle board,
MDF, wood fiber boards, HDF, WPC,
lightweight panels, composite materials



excellently suited for:
aluminum, NF-metals,
composite materials



well suited for:
thermoplastics, thermo-
setting plastics, elastomers,
composite materials

Wood fibre:



Melamine laminated particle board:



Alu Hollow profile:



HPL laminate:



Ø D [mm]	B [mm]	b [mm]	Ø d [mm]	Z	tooth configuration	NL	Hook angle [°]	Order-No.
130	2,8	2,2	20	36	TR-F		-6	58115027
150	2,8	2,2	20	42	TR-F	2/6/32,5	-6	58115002
160	2,2	1,6	20	42	TR-F	2/6/32,5	-6	58115004
160	2,2	1,6	20	56	TR-F	2/6/32,5	-6	58115042
160	2,8	2,2	30	42	TR-F	2/7/42	-6	58115026
165	2,8	2,2	20	48	TR-F	2/6/32,5	-6	58115044
180	2,8	2,2	20	48	TR-F	2/6/32,5	-6	58115007
180	2,8	2,2	30	48	TR-F	2/7/42	-6	58115008
190	2,8	2,2	20	54	TR-F	2/6/32,5	-6	58115009
190	2,6	2,0	20FX	58	TR-F	Fast-Fix	-6	58115033
190	2,8	2,2	30	54	TR-F	2/7/42	-6	58115010
200	2,8	2,2	30	54	TR-F	2/7/42	-6	58115011
210	2,8	2,2	30	54	TR-F	2/7/42	-6	58115012
216	2,8	2,2	30	60	TR-F	2/7/42	-6	58115024
216	2,8	2,2	30	80	TR-F	2/7/42	-6	58115034
220	2,8	2,2	30	54	TR-F	2/7/42	-6	58115021
230	2,8	2,2	30	64	TR-F	2/7/42	-6	58115014

Contact
Stehle

T +49 (0) 7451 / 93 222
F +49 (0) 7451 / 93 444

Date 02/2016

info@stehle-int.com
www.stehle-int.com